MINI GAC® 2500 Grain moisture analyzer

The most accurate handheld moisture tester that provides fast and easy results. Now with 149 MHz - UGMA technology to match the new moisture testers at the elevator.

Measuring grain moisture straight from the field has never been easier than with the DICKEY-john mini GAC[®] 2500 handheld grain moisture analyzers. This handheld moisture tester offers the highest level of accuracy in its class, plus the mini GAC is fast and easy to use.

Features and Benefits:

- Simplifies operation with menu-driven interface
- Eliminates pre-weighing with an internal scale
- Avoids cumbersome screw caps that can cause grain damage and oily residue
- Easily loads calibrations with a USB
- Tests hot or cold grain between 32 and 122°F (0 50°C)
- Receives accurate measurements in a variety of conditions with automatic temperature compensation

Backed by the power of DICKEY-john:

When you buy a mini GAC 2500, you get all the dependability and value you expect from DICKEY-john products. DICKEY-john's advanced technology and superior electronics are backed by a team of expert, in-house mechanical, electrical, software, and test engineers. All mini GACs are manufactured by DICKEY-john under strict quality control in an ISO 9001 certified facility. Made in the U.S.A.







Unit Specifications

Measurement method:

Moisture range: Grain temperature: Temperature difference:

Temperature compensation: Grain type: Sample size: Display: Analyzer height:* Analyzer width:* Analyzer depth:* Weight (total): Measured parameters:

149 MHz - UGMA technology, internal scale, temperature 5 - 45 % (depending on grain type) 32 - 122° F (0 - 50° C) 36° F (20° C) instrument to grain sample automatic whole grain, no sample preparation 1 pint (0.47 L) LCD (106 x 56 pixels) 11.9 in (30.2 cm) 4.8 in (12.2 cm) 8.3 in (21.1 cm) 2 lbs 7 oz (1.1 kg) moisture, grain temperature and test weight

Grain Temperature

Measurement Specification

Accuracy:	1.0° F or 0.5° C
Temperature resolution	0.1 ° F or 0.1 ° C
Test Weight Specifications	11 /1 / 1 /1 /1
Repeatability:	0.5 lb/bu (0.6 kg/h)
	in commercial trade range,
	depending on grain type
Test weight resolution:	0.1 lb/bu (kg/hl)

Other Specifications

Operating temperature:	40 - 113° F (5 - 45° C)
Humidity:	5 - 95% non-condensing
Power:	9 VDC battery (installed)

* Measured with loader/striker in carrying position. ** Bluetooth® where available

Moisture Measurement Specifications

Moisture repeatability:	0.3% moisture, depending on grain type, in commercial trade range, typical
Moisture resolution:	0.1% moisture





5200 Dickey John Road Auburn, IL 62615 www.dickey-john.com +1 217-438-3371 +1 217-438-6012 fax ©2017 DICKEY-john The Bluetooth[®] word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc.

DICKEY-john, the DICKEY-john Logo and GAC are registered trademarks of DICKEY-john.

5001797 Rev B

